

<b>Model No</b>	LOL0215
<b>Application</b>	Accent
<b>Description</b>	Die Cast Aluminium Uplight
<b>Lamp</b>	MR-16 LED
<b>Wattage</b>	5W LED
<b>Voltage</b>	12V AC

<b>Finish</b>	Wide range of powdercoat colours and finishes
<b>Mounting</b>	Spike Mount*
<b>Fasteners</b>	Stainless steel screws
<b>IP</b>	TBA
<b>Weight</b>	TBA
<b>Beam</b>	25° , 36° or 60°

<b>Dimensions</b>	148.6 x 65.7
mm	L x W

#### Notes

\* tree mount junction box or wall mount canopy options available

#### Detailed description

This low voltage up & accent fixture is constructed of die-cast, copper-free aluminum for strength and reliability. The fully rotatable shroud is compatible with accessories like lenses & louvers. The housing is equipped with an oversized silicone O-ring to protect against moisture and dust intrusion. At the base of the housing is a high temperature silicone diaphragm gasket which incorporates an innovative air valve that prevents a vacuum from forming within the fixture during dramatic temperature changes. A clear, tempered, shock and heat-resistant, soda-lime glass lens safeguards the lamp and optics. A super durable polyester powder coat finish is applied and is available in a variety of colors or finishes. The intelligently engineered fully adjustable knuckle is made from injection-molded, fiber-reinforced composite which effectively isolates the fixture from the harmful corrosive soil.

**Note:** All dimensions and other specifications can change without notice. Please contact Light On Landscape to confirm the availability and current specifications of this luminaire.

**Installation:** Light On Landscape strongly recommend that all luminaires be correctly installed and maintained. Failure to do so will result in the voiding of the manufacturer's warranty and the reduced efficiency, performance and life of the fixture. To eliminate voltage drop, we advise that the recommended UV stabilized cable and run lengths are used, along with soldered joints, heat shrink connectors and quality lamps.

